## **PRODUCT DATA SHEET**

# **Application Papers and Application Film**

issued: 9/2018 Revision: 1

# Avery Dennison<sup>®</sup> Application Paper 300 - High Tack

Description:

Carrier Adhesive : saturated paper, white : synthetic rubber

## Features:

- High tack adhesive
- Semi-transparent carrier
- Excellent water resistance

### Recommendations for use:

- Specially developed for small and medium sized graphics
- Transfer of large cut out letters and printed decals
- Suitable for dry and wet application

# Avery Dennison<sup>®</sup> Application Paper 250 - Medium/High Tack

Description:

Carrier Adhesive : saturated paper, white : synthetic rubber

### Features:

- Medium to high tack adhesive
- Good ageing properties and UV resistance
- Semi-transparent carrier
- improved adhesion to paper or film release liners

Recommendations for use:

- Specially developed for signs or graphics with larger areas of exposed liner
- Excellent for hard-to-transfer vinyls with tight release liner
- Small and medium-size letters and printed decals
- Specialty vinyls
- Thermal die-cuts

# Avery Dennison<sup>®</sup> Application Tape 300 - High Tack

#### **Description:**

Carrier Adhesive

: Embossed Polyethylene film, transparent

e : Polyacrylate

#### Features:

- High clarity for accurate registration
- High tack, ideal for difficult to transfer films
- Embossed micro channels for bubblefree lamination
- High dimensional stability and lay flatness
- No adhesive residues with wet applications and no water whitening
- Longer shelf life for ready to apply graphics

### <u>Recommendations for use:</u> Textured and matte finish vinyl films

- Fine lettering
- Multicolour overlays needing accurate registration
- Thermal die-cuts





## **PRODUCT CHARACTERISTICS**

Avery Dennison® Application Paper 300 High Tack

Carrier material (paper) Colour Caliper (micron) ISO 538 Adhesive tack level

Saturated White 100

high

medium/high

Avery Dennison® Application Paper 250 Medium/High Tack

Saturated White 100

Applicaton Tape 300 High Tack

PE-film Transparent 106

Avery Dennison®

high

## Temperature Range (°C)

Application Temperature Service Temperature

+ 10 °C + 10 °C to + 40 °C

## General:

Shelf life

Stored at 22 °C/ 50-55% RH

1 years

#### Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

#### Warranty

Avery Dennison<sup>®</sup> branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All Avery Dennison® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available

on request.

#### Test methods

More information about our test methods can be found on our website.





23 avenue Paul Duplaix Z.I d Prat - 56000 VANNES 02 97 01 22 90 numerique www.idnumerique.fr