

NEW



FLOOR Vinyl
by Gerflor

**THE PRINTABLE
FLOORING**

Dedicated to **communication events**
(stand, advertising, POS communication)
and **decoration items business**.

Printable, ideal to **personnalize** your floor.

Compatible with **UV large-size
digital printer, latex and
digital cutting solution**.

id.
numerique

Gerflor
theflooringgroup

Made in France by Gerflor,
leader of professional and housing flooring solution
for more than 80 years.





EASY TO LAY:
indoor, with
double-sided adhesive,
on all subfloor
(wood, concrete, tile...)



**ECONOMIC AND
COMFORTABLE,**
absorbs noises
and shocks,
slip-resistant (R10)

FLOOR Vinyl

by Gerflor

ROLL WIDTH

1,5 M

2 M

3 M

DESCRIPTION

Total thickness	EN ISO 24346 (EN 428)	mm	2.50		
Wearlayer thickness	EN ISO 24340 (EN 429)	mm	0.15		
Weight / Mass per unit area	EN ISO 23997 (EN 430)	g/sqm	1485		
PU Surface treatment	-	-	no		
Mechanical embossing	-	-	yes		

CLASSIFICATION

Norm / Product specification	-	-	EN ISO 26986		
Fire rating - Classification Glued down wood support	EN 13501-1	class	C _{fl} -s1		
Slip resistance wet : ramp test with oil	DIN 51 130	class	R10		

PERFORMANCES

White index	WI-ASTM	%	≥ 55		
Wear Group	EN 660-2	group	T		
Dimensional stability after exposure to heat	EN ISO 23999 (EN 434)	%	0.05		
Residual indentation (requirement)	EN ISO 24343-1 (EN 433)	mm	< 0.35		
Colour fastness	EN 20 105-B02	degree	> 6		

PACKAGING

Standard Length of sheet	EN ISO 24341 (EN 426)	ml	30		
Minimum Length of sheet	EN ISO 24341 (EN 426)	ml	15		
Cardboard Core diameter (inside)	-	mm	100* ou 76,8*		100*
Total weight of a reel	-	kg	67	90	134
Total diameter of a reel	-	mm	330		
Bulk transportation	-	-	yes		
Pallet dimension	-	mm	in option (6 rolls/palett)		no
			1100 x 2000	1100 x 2000	-

ENVIRONMENT

TVOC after 28 days	EN ISO 16000-6	µg/m ³	< 100		
French norm	-	-	A+		
Floorscore (US norm)	-	-	OK		

MARQUAGE CE

CE	EN 14041					R10
----	----------	--	--	--	--	-----

* Core diameter tolerance: -0,4 mm / +0,1 mm

