

Protac™

Anti-Graffiti

Protac™ Anti-Graffiti is a 0.8 mil (20µ) high gloss PET film with an anti-graffiti coating on the surface, coated on the other side with a high coat weight pressure sensitive, solvent acrylic adhesive that is protected by a one side siliconized PET release liner. Both the film and adhesive contain UV stabilizers, which protect against UV degradation. The high coat weight and strength of the adhesive makes Protac™ Anti-Graffiti ideal for laminating over UV inks as well as (eco) solvent and latex prints.

- IDEAL FOR A VARIETY OF APPLICATIONS, INCLUDING BUS SHELTERS, CONSTRUCTION BARRICADES AND OUTDOOR ADVERTISING LOCATIONS IN HIGH TRAFFIC AREAS
- PROTAC™ ANTI-GRAFFITI HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	High Gloss PET
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	0.8 mil (20µ)	2 mil (50µ)
Adhesive Layer	1.2 mil (30µ)	
Film/Adhesive Ratio	0.8:1.2	
UV Protection Factor	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image	
Outdoor Durability	5 Years	
Peel Strength (20 min, FTM1)	15 N/25mm	
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013