

# Polar®

## Chrome

Polar® Chrome is a 75 micron printable reflective silver PET film with a clear permanent acrylic adhesive. Create engaging displays and signage with this bold reflective film. Polar® Chrome is ideal for indoor/short-term outdoor signage, billboards and exhibitions hall displays, POS displays, bus or subway advertisements.

- IDEAL FOR PROMOTIONAL GRAPHICS OR DECALS
- SUITABLE FOR INDOOR OR SHORT-TERM GRAPHICS
- EYE-CATCHING REFLECTIVE FACE FILM

Product Code: PCH

**75** Silver Reflective  
micron PET

■  
Satin



(Eco) Solvent  
Latex  
UV



Clear  
Permanent  
Adhesive



Widths up to 60 in

YEARS DURABILITY  
**3**

INTERIOR

YEARS DURABILITY  
**2**

EXTERIOR\*



STRIKING REFLECTIVE FILM



## APPLICATIONS

SIGNAGE

BILLBOARDS

EXHIBITION HALLS

RETAIL & POP DISPLAY



# DRYTAC®

ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# Polar®

## Chrome

Polar® Chrome is a 3 mil (75µ) premium, silver satin PET film with a clear permanent pressure sensitive acrylic adhesive that is protected by a siliconised 1 side PET liner. Polar® Chrome provides a superb printing surface for eye-catching color graphics, interior or exterior.

- EYE-CATCHING REFLECTIVE FACE FILM
- CAN BE USED TO CREATE ULTRA-REFLECTIVE LABELS
- IDEAL FOR POSTERS, BILLBOARDS, EXHIBITION HALL DISPLAYS, TRADE SHOW, POP DISPLAYS AND BUS OR SUBWAY ADVERTISEMENTS

### INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Silver Satin PET
<b>Adhesive</b>	Clear Permanent Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconised 1 Side PET

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3 mil (75µ)   4 mil (100µ)
<b>Adhesive Layer</b>	1 mil (25µ)   (100µ)
<b>*Outdoor Durability</b>	2 Years (ink dependent - see warranty for details)
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	-4°F to 266°F (-20°C to 130°C)
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	50°F to 77°F (10°C to 25°C); 20% Relative Humidity

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)