ChalkMate®

Permanent

ChalkMate® Permanent is a 125µ (5 mil) durable, printable PVC film with a traditional black chalkboard finish and permanent acrylic adhesive. It works well when creating chalkboard walls or making unique, custom chalkboard decals from die cut shapes or designs. Installs on most smooth surfaces.

- DURABLE VINYL FILM THAT CAN BE WRITTEN ON WITH STANDARD CHALK OR LIQUID CHALK MARKERS
- IDEAL FOR TEACHING ENVIRONMENTS SUCH AS SCHOOLS OR DAYCARE CENTERS
- EXCELLENT OPTION FOR WRITING MENUS OR PRICES IN DELIS, PUBS AND GROCERY STORES
- POPULAR FOR CHILDREN'S
- PLAYROOMS
- GREAT FOR CAPTURING IDEAS OR

 NOTES IN MEETING ROOMS

EFFECTIVE TOOL FOR SHOPPING MALL PROMOTIONS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

| Film | Black PVC |
|---------------|---|
| Adhesive | Permanent Acrylic |
| Release Liner | 93 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper |

PRODUCT CHARACTERISTIC

| Film Thickness | 5 mil (125µ) |
|-----------------------------|--|
| Adhesive Layer | 0.8 mil (20μ) |
| Film/Adhesive Ratio | 5:0.8 |
| UV Protection Factor | Not Applicable |
| Outdoor Durability | Not Applicable |
| Application Temperature | >41°F (5°C) |
| ServiceTemperature Range | -4°F to 203°F (-20°C to 95°C) |
| Shelf Life | 2 years |
| Storage Conditions | 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity |

Special Regulatory Information: This product is formulated to be compliant with the California Proposition 65 regulation. It contains no zinc, lead, cadmium, or other heavy metals. This product is formulated to be phthalate-free.



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com Tel: +44 (0) 117 958 6500

Canada

30 Driver Road, Brampton, Ontario, L6T 5V2, Canada toronto@drytac.com

Tel: +1 800.353.2883

USA

5401-B Eubank Road, Sandston, Virginia, 23150, USA customerservice@drytac.com

Tel: +1 800.280.6013