

Seemee Loop Frontlit

Light

Technical properties

| | |
|----------------------------|--|
| Product reference | B4219 |
| Application | Banner, Billboard, building wraps |
| Printing technology | UV, Latex |
| Support cloth DIN ISO 2076 | 100% rPET |
| Type of coating | 100% rPolymers from post-consumer-waste |
| Weight DIN EN ISO 2286-2 | 320 g/m ² |
| Width DIN EN ISO 2286-1 | 160 cm - 250 cm - 320 cm - 500 cm 63 in - 98 in - 126 in - 197 in |

Roll length

| | |
|----------------|------------------|
| For all widths | 50 lm - 54.68 yd |
|----------------|------------------|

Physical properties

| | |
|--|---------------|
| Tensile strength (warp/weft) DIN EN ISO 1421 | 180 / 150 daN |
| Tear strength (warp/weft) DIN 53363 | 60 / 40 daN |

Fire resistance

| | |
|----------------------|----------------|
| Rating | DIN 4102 B1 |
| Euroclass EN 13501-1 | B-s1-d0 |

Management system

Quality: ISO 9001 • Environment: ISO 14001 • Energy: ISO 50001

Certifications, labels, warranty



¹ Summarizes the group's CSR project focused on human, to align economic performance and positive impact.

The technical data above are averaged values with a +/-5% tolerance.

The purchaser of our products is responsible for their application or transformation in relation to possible third party rights. The purchaser of our products is responsible for their installation in compliance with the standards, working practices and safety regulations of their destination country. Please refer to our warranty document with regard to contractual liability.

Values quoted in this document are commonly used test results for design purposes. They are given for information only in order to offer our customers optimum usage of our products. Our products are subject to improvements resulting from technical developments and we reserve the right to modify their characteristics at any time. The purchaser of our products is responsible for checking the above data.

The colours and textures presented are included for information only.

Loop Frontlit

Light

